

Product Overview - O.D. Models

Available features:

- Arm Retraction For Part Loading
- Fixed or Follow Down Operation
- 2-Axis Centerline Adjustment
- Visible Zero Adjustment Screws
- Upper Arm Gage Clearance
- Position Feedback Sensors
- Lower Mounting Rail

*Side Mount Cylinder

*** See Data Sheet For Specific Features of Each Model ***



OD Grinding Models - Direct Mounted Pad Design

Model		GR-081		GC28601A		GC29222Y		GR-3520V		GR-6030V	
Clamp Range	mm	1 – 8**		2.5 – 15**		2 – 27		15 – 35		20 - 60	
Pad Set 1		1 – 3		2.5 – 8		2 – 7		15 – 30		20 - 50	
Pad Set 2			2.5 - 8		5 – 10.5		7 – 27		20 - 35		30 - 60
Pad Set 3					9.5 - 15		4 – 21				

** Limited Clamping Force - Light Duty Only

OD Grinding Models - Nest Mounted Pad Design

Model		GR-055V			GR-115V			GR-320V-W		
Maximum Size	mm	40			60			90		
Nest Set 1		10 – 20			15 – 30			10 – 30		
Nest Set 2			20 – 30			30 – 45		30 – 50		
Nest Set 3				30 - 40		45 - 60			50 - 70	
Nest Set 4										70 – 90

OD Grinding Models - Nest Mounted Pad Design

Model		GC26345A			GC32363A			GC32615A		
Maximum Size	mm	120			150			210		
Nest Set 1	mm	30 – 60			30 – 70			30 – 90		
Nest Set 2	mm		60 – 90			70 – 110			90 – 150	
Nest Set 3	mm			90 - 120			110 – 150			150 - 210

Contact sales@arobotech.com for free assistance

- Model selection
- Process review
- Special models
- 3D Models
- Accessories
- Machine integration
- Modifications
- Special features
- Mounting Bases
- Spare Parts